SAFETY DATA SHEET.

Issuing date 21-Jul-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier Product name

10328 COPPER ANTI SEIZE

Recommended use of the chemical and restrictions on use

Product code

F00331

Product Type Synonyms Extremely flammable aerosol None

Supplier's details

Recommended Use Uses advised against

ANTI-SEIZE COMPOUND. No information available

Manufactured For:

Dixie Packaging & Seal Company 1900 Elm Tree Drive Nashville, TN 37210

Emergency telephone number Chemical Emergency Phone Number Manufacturer American Jetway Corporation 34136 Myrtle Street Wayne, MI 48184-0126

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

Emergency Overview

<u>GHS Label elements, including</u> precautionary statements

DANGER

Hazard Statements

Causes skin irritation May cause respiratory irritation. May cause drowsiness or dizziness May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated



Appearance opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Specific treatment (see first aid on this label) IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse If skin irritation occurs: Get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Very toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HEPTANE	64742-49-0	40-50
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
HYDROTREATED HEAVY NAPHTHENIC	64742-48-9	10-20
GRAPHITE	7782-42-5	1-10
COPPER	7440-50-8	1-10
ALUMINUM POWDER	7429-90-5	1-10
ZINC OXIDE	1314-13-2	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Notes to physician	Treat symptomatically.	
Indication of immediate medical attention and special treatment needed, if necessary		
Main Symptoms	Causes skin irritation. May be fatal if swallowed and enters airways. May cause respiratory irritation.	
Most important symptoms/effects, acute and delayed		
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.	

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

Specific hazards arising from the chemical

No information available.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas.Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cands. Wear protective gloves/clothing and eye/face protection.

Environmental precautions

Environmental precautions Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not
	puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage	Keep container tightly closed in a dry and well-ventilated place. Keep away from open
conditions	flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents.

Aerosol Level

3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Revision Date 21-Jul-2015

HEPTANE	TLV: 400 ppm	TWA: 500 ppm	-
64742-49-0 PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	STEL: 500 ppm 74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m³ TWA: 2.5 mg/m³ natural respirable dust
COPPER 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist
ALUMINUM POWDER 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust TWA: 5 mg/m³ Al
ZINC OXIDE 1314-13-2	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face ProtectionSafety glasses with side-shields.Skin and body protectionChemical resistant apron. Protective gloves.Respiratory protectionIf exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved
respiratory protection should be worn. Positive-pressure supplied air respirators may be
required for high airborne contaminant concentrations. Respiratory protection must be
provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Appearance Color	Aerosol opaque Copper	Odor Odor Threshold	Solvent No information available
Property_	Values	Remarks • Methods	
noperty DH	No information available	Kemarks • Methous	
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-97 °C / -142 °F	Based on propellant	
Evaporation rate	No information available	Daoba on propolati	
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit	No information available		
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	0.71		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/wat	erNo information available		
Autoignition temperature	No information available	Not applicable	
Decomposition temperature	No information available		
Viscosity	No information available		
Explosive properties	No information available		
Other information			
VOC Content(%)	73.69		
10. STABILITY AND REACTIVITY			

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes.
Skin contact	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
Ingestion	May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEPTANE	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
64742-49-0			
HYDROTREATED HEAVY	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
NAPHTHENIC			
64742-48-9			
ZINC OXIDE	> 5000 mg/kg (Rat)	-	-
1314-13-2			

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, tiredness, nausea, and vomiting. Causes respiratory irritation. Causes skin and eye irritation.Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	Irritating to eyes.
Irritation	Irritating to eyes, respiratory system and skin.
Sensitization	None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	There are no known carcinogenic chemicals in this product.
Reproductive toxicity	This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic	May cause respiratory irritation. May cause drowsiness and dizziness.
toxicity (single exposure)	
Specific target organ systemic	None under normal use conditions.
toxicity (repeated exposure)	
Chronic toxicity	May cause adverse liver effects.
Target Organ Effects	Central Vascular System (CVS), Eyes, Kidney, Liver, Respiratory system, Skin.
Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or
	fatal.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	0% of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	5116 mg/kg
ATEmix (dermal)	5966 mg/kg
ATEmix (inhalation-gas)	760157 mg/l
ATEmix (inhalation-vapor)	51 mg/l

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	-	2200 mg/L LC50 Pimephales promelas 96h	-	-
COPPER 7440-50-8	0.0426 - 0.0535 mg/L EC50 Pseudokirchneriella subcapitata 72h static 0.031 - 0.054 mg/L EC50 Pseudokirchneriella subcapitata 96h static	0.0068 - 0.0156 mg/L LC50 Pimephales promelas 96h 0.3 mg/L LC50 Pimephales promelas 96h static 0.052 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.112 mg/L LC50 Poecilia reticulata 96h flow-through 0.2 mg/L LC50 Pimephales promelas 96h flow-through 0.3 mg/L LC50 Cyprinus carpio 96h semi-static 0.8 mg/L LC50 Cyprinus carpio 96h static 1.25 mg/L LC50 Lepomis macrochirus 96h static	-	0.03 mg/L EC50 Daphnia magna 48h Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

log Pow
2.8
-

Other adverse effects

No information available

Do not re-use empty containers.

13. DISPOSAL CONSIDERATIONS

Waste Disposal MethodsThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR
261).

Contaminated packaging

14. TRANSPORT INFORMATION

DOT Ground Marine Pollutant	CONSUMER COMMODITY ORM-D or LIMITED QUANTITY This product contains a chemical which is listed as a severe marine pollutant according to DOT.
ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
IMDG	UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HEPTANE	Х	Х	Х	Х	Х	Х	X	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	X	Х	Not listed	Х	Х	X	Х
HYDROTREATED HEAVY NAPHTHENIC	Х	X	Х	х	Х	Х	X	Х
GRAPHITE	Х	Х	Х	Not listed	Х	Х	X	Х
COPPER	Х	Х	Х	Not listed	Х	Х	Х	Х
ALUMINUM POWDER	Х	Х	Х	Not listed	Х	Х	X	Х
ZINC OXIDE	Х	Х	Х	Х	Х	Х	X	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
COPPER - 7440-50-8	7440-50-8	1-10	1.0
ALUMINUM POWDER - 7429-90-5	7429-90-5	1-10	1.0
ZINC OXIDE - 1314-13-2	1314-13-2	1-10	1.0
SARA 311/312 Hazard Categories		·	
Acute Health Hazard	Yes		
Chronic Health Hazard	Yes		
Fire Hazard	Yes		
Sudden Release of Pressure Hazard	Yes		
Reactive Hazard	no		

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COPPER 7440-50-8		Х	X	
ZINC OXIDE 1314-13-2		Х		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Revision Date 21-Jul-2015

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
COPPER	5000 lb		RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any known Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
GRAPHITE 7782-42-5	Х	X	X
COPPER 7440-50-8	Х	X	X
ALUMINUM POWDER 7429-90-5	Х	X	X
ZINC OXIDE 1314-13-2	Х	X	X

EPA Pesticide Registration Number Not applicable

material or in any process, unless specified in the text.

<u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION						
NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards		
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B		
Prepared By	American Jetway 34136 Myrtle Street Wayne, MI 48184					
	Tel.734-7	721-5930				
Issuing date	21-Jul-2(015				
Revision Date	21-Jul-20	015				
Revision Note						
No information available						
Disclaimer						
publication. The inform	nation given is design	ed only as a guide for sa	owledge, information and afe handling, use, process warranty or quality specif	ing, storage,		

End of Safety Data Sheet

relates only to the specific material designated and may not be valid for such material used in combination with any other